

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIOROOM
Fire Resistant Safety Cabin**

Fire-resistant room for the storage of large quantities of hazardous materials and the enclosure of production facilities in operation. The 42 mm construction method of prefabricated panels results in fast and cleanly built separated fire compartments. Benefits: chemically highly stable internal and external surfaces, simple construction, reconstruction and extensions. The room always has a threshold-free access and can be equipped with standard drip pans according to the provisions of the Federal Water Act. The room provides 90 minutes fire resistance.

Function

- Fire resistance 90 minutes: fire resistant
- EI 90/F 90 classification
- Fire chamber test, according to DIN 4102-2

Construction

- Room with high mechanical and chemical resistance
- Barrier-free access with pallets, drums and compressed gas cylinders
- Door(s) with 3D stainless steel strips, 3-point locking system, prepared for profile cylinder
- Suitable for the storage and removal of flammable liquids, acids and alkalis
- Room may be equipped with lighting, ventilation equipment, racks and drip pans
- Delivered on pallets, assembly on site

Material characteristic

- Building material with surface coating on both sides, classified A2 – s1, d0 non-combustible
- Standard surface CP laminate is chemically highly stable and moisture-resistant
- Colour light grey, similar to RAL 7035, edges and bevels in different colour

Options

- Doors or entire body in alternative RAL colours / surfaces, see pages 16/17
- Stainless steel encasement in V4A 1.4571
- Design with anti-burglary protection according to WK 2
- Smoke proof
- Ventilation flap
- Fire resistant cable compartment
- Door hold-open device
- Explosion protected smoke detector
- Door handles, locking cylinder
- Door damper
- Door closer for single leaf doors
- Door closer for double leaf doors
- Motor lock
- Panic hardware with panic function B
- Electronic door closing systems

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

PRIOROOM GSL is offered on a project-by-project basis

- Element-External dimension (H x B x T) in mm:
- Surface:
- Door stop (DIN L / DIN R):
- Number door:
- Door clearance height in mm:
- Door clearance width in mm:
- Number door leaf:
- Number fixed leaf:
- Number active leaf:
- Storage volumen number euro palette:
- Storage volumen number drums:
- Options:

Typ: PRIOROOM

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: 06181 / 3640 0
Fax : 06181 / 3640 230