

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10      1      **PRIODOOR ETX A – EI 90**  
**Inspection door, flush with the adjacent areas**

Inspection door for flush mounting in GRP shaft walls with no visible frame. The lockable and sealed door with an aluminium frame that can be plastered over is suitable for compliant partitioning of small and large installation shafts and the partitioning of measuring equipment and distributors in escape and rescue routes. Quick and easy installation for easy access to shaft. The closure is smoke-tight and provides a fire resistance of 90 minutes.

**Function**

- 90 minutes fire resistance, fire resistant
- EI 90/F 90; classification
- Smoke protection
- Leak-proof closing
- Protection rating according to IP 42
- Safety class II

**Construction**

- Inspection door with high mechanical and chemical resistance
- Flush mounting in 2 x 20 mm GRP shaft wall or 2 x 25 mm when planked
- Installed depth < 100 mm in metal stud wall
- Single-leaf design, Door stop position DIN right
- Circumferential aluminium frame with plaster edge
- Circumferential smoke and fire seals,
- expand automatically in the event of a fire
- Door closes flush with frame, opening angle ca. 180°
- Locking system with single cylinder

**Material characteristic**

- Building material with surface coating non-combustible, classification A2 – s1, d0
- Standard CPL surface is highly chemically resistant and sensitive to moisture
- Colour light grey, similar to RAL 7035, edges and bevels in different colour

**Scope of delivery**

- Door leaf with stainless steel hinges and box staple
- Aluminium frame, corner connection, fire and smoke seal
- Profile single cylinder
- Torque plate and fastening clip, Assembly blocks

**Options**

- All PRIORIT surfaces
- Door lock cylinder rosette
- Profile single cylinder – simultaneous locking
- Artificial ventilation

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Element-External dimension  
(H x B) in mm: .....

Rough opening BRM  
(H x B) in mm: .....

Surface: .....

Weight: .....

Wall type: .....

Options: .....

**Typ: PRIODOOR ETX A**

**Fabrikat: PRIORIT AG**  
[www.priorit.de](http://www.priorit.de)  
**Tel.: +49 6181 3640-0**  
**Fax : +49 6181 3640-230**