

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIOELEC EW – 30 Minutes
Electro Wall Recessing Cabinet**

PRIORIT electro wall recessing cabinet in single-leaf design, suitable for a smoke-tight and fire-resistant separation of electrical distributors in rescue routes (fire load insulation). The housing is made of non-combustible building material class A2 – s1, d0. As a standard the cabinets have top and bottom cable entries. The inside dimensions are based on the electro-technical standard distribution panels and mounting plates.

Function

- Fire resistance of 30 min, fire-retardant
- Classification: suitable for fire load insulation of 30 minutes
- Smoke protection
- Protection rating according to IP 42
- Safety class II

Construction

- Empty case for wall recessing
- Door can be unhinged for weight reduction during transport
- Door hinge right, may be changed on site to the left
- Door closes flush with body, opening angle ca. 180°
- 2-point door locking with swing lever and double-bit cylinder
- Circumferential fire seals automatically expand in the event of a fire
- Cable entries top + bottom
- Attachment points for electric installations

Material characteristic

- Building material with surface coating non-combustible, classification A2 – s1, d0
- Standard CPL surface is highly chemically resistant and sensitive to moisture
- Colour light grey, similar to RAL 7035, edges and bevels in different colour

Options

- All PRIORIT surfaces
- EDF fixing cross beam

Element-External dimension

(H x B x T) in mm:

Surface:

Weight:

Door hinge

(DIN L / DIN R):

Panel height:

LV:
Objekt :

Datum: 01.08.16
Seite: 2

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Panel width:

Unit space:

Options:

Typ: PRIOELEC EW

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: +49 6181 3640-0
Fax : +49 6181 3640-230