

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10	1	<b>PRIOCAB Typ30</b> <b>Safety Cabinets according to DIN EN 14470-1</b>		
----	---	----------------------------------------------------------------------------	--	--

Fire-resistant type 30 safety cabinet, available in two sizes (single- and double-leaf) for proper storage of flammable liquids and solid materials in work areas.

Type 30 safety cabinets, tested and approved in accordance with EN 14470-1, offer a fire resistance rating of 30 minutes, and are GS (geprüfte Sicherheit - tested safety) certified.

The single-layer structure of the body and door give the cabinet a high level of mechanical strength. The high-quality interior and exterior surfaces are easy to clean. Feet are integrated as a standard feature and can be adjusted from the inside, making it easy to set up and align the cabinets. The base has clearance for a lift truck or forklift to drive underneath, allowing the cabinets to be moved and transported easily.

#### Function

- Fire resistance 30 minutes
- GS Certificates
- Safety cabinet Typ30 according to EN 14470-1
- Suitable for the storage of inflammable fluids

#### Construction & Equipment

- Safety cabinet with high-quality surface inside and outside
- Single layer wall structure
- Available sizes: Single and double-leaf version (width 595 mm and 1195 mm)
- Self-closing ventilation openings at the cabinet top operate in the event of a fire, connections DN 100 mm
- Door closer with integrated hold-open system and thermocouples for automatic door closure in the event of fire
- Different equipment variants
- Fittings adjustable in 32 mm hole spacing
- Floor pan with perforated plate insert for use as a fourth storage level
- Grounded tank bottom, tilt resistant with a central hole for systematic removal of leakage
- With ground clearance for easy lifting, height 100 mm with removable front panel

#### Material & Surface

- Homogeneous building material, single-layer construction
- Standard surface CP laminate
- Surface light grey, similar to RAL 7035
- Easy to clean

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

**Options**

- Doors and entire body in alternative RAL colours / surfaces, on request
- Tank bottoms, max. load 75 kg
- Fully extendable shelf, max. load 75 kg
- Load increase to 150 kg
- Floor pan incl. perforated plate insert
- Perforated plate insert
- Equipment in stainless steel on request
- Fine (pre)filter for EBEL:VENT-EN-U (replacement)
- Replacement active charcoal filter for EBEL:VENT-EN-U
- Connection adaptor for EBEL:VENT-EN-U
- Recirculated air attachment, ready to plug in

Element-External dimension  
(H x B x T) in mm:

.....

Surface:

.....

Weight:

.....

Options:

.....

**Typ: PRIOCAB Typ30**

**Fabrikat: PRIORIT AG**  
[www.priorit.de](http://www.priorit.de)  
**Tel.: 06181 / 3640 0**  
**Fax : 06181 / 3640 230**