

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIOCAB Typ90 - double-leaf
Safety Cabinets according to DIN EN 14470-1**

Fire-resistant type 90 safety cabinet for proper storage of flammable liquids and solid materials in work areas.

Type 90 safety cabinets, tested and certified in accordance with EN 14470-1, offer a fire resistance rating of 90 minutes, and are GS (geprüfte Sicherheit - tested safety) certified.

The cabinets offer an extraordinary level of stability and a long service life. The base material is high-density, and does not represent a fire load.

The high-quality interior and exterior surfaces are easy to clean. Feet are integrated as a standard feature and can be adjusted from the inside, making it easy to set up and align the cabinets. The base has clearance for a lift truck or forklift to drive underneath, allowing the cabinets to be moved and transported easily. The doors of the safety cabinets close automatically in case of a fire.

Function

- GS Certificates
- Fire resistance 90 minutes
- Safety cabinet Typ90 according to EN 14470-1
- Suitable for the storage of inflammable fluids

Construction & Equipment

- Safety cabinet with high-quality surface inside and outside
- Single-layer doors and walls made of homogeneous solid material
- Double-leaf version (width 1195 mm)
- Self-closing ventilation openings on the top of the cabinet operate in the event of fire, connections DN 100 mm
- Double leaf cabinets with free-wheeling doors: thermally induced closure in the event of a fire
- Different equipment variants
- Fittings adjustable in 32 mm hole spacing
- Floor pan with perforated plate insert for use as a fourth storage level
- Grounded tank bottom, tilt resistant with a central hole for systematic removal of leakage
- With ground clearance for easy lifting, height 100 mm with removable front panel

Material & Surface

- Standard surface CP laminate
- Building material with surface coating, classified A2 – s1, d0: non-combustible
- Surface light grey, similar to RAL 7035

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Options

- Doors and entire body in alternative RAL colours / surfaces, on request
- Tank bottoms, max. load 75 kg
- Fully extendable shelf, max. load 75 kg
- Load increase to 150 kg
- Floor pan incl. perforated plate insert
- Perforated plate insert
- Equipment in stainless steel on request
- Fine (pre)filter for EBEL:VENT-EN-U (replacement)
- Replacement active charcoal filter for EBEL:VENT-EN-U
- Single cable and pipe-penetration
- Recirculated air attachment, ready to plug in
- Extract air attachment, ready to plug in

Element-External dimension
(H x B x T) in mm:

Surface:

Weight:

Options:

Typ: PRIOCAB Typ90 – double-leaf

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: 06181 / 3640 0
Fax : 06181 / 3640 230