

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10      1      **PRIOCONT  
Fire-Resistant Container**

Fire-resistant container to store two IBC containers or six 200l barrels on Euro pallets. The homogeneous, solid material has high-quality, easy to clean interior and exterior surfaces. The base has sufficient clearance to drive a forklift underneath for transportation. The container is smoke proof in accordance with DIN 18095 and offers a fire resistance of 90 minutes.

**Function**

- Complies with the requirements of the Technical Regulations for Hazardous Material 510, Act on the Regulation of Matters Relating to Water, Hazardous Materials Safety Regulations,
- Fire resistance 90 minutes: fire resistant
- EI 90/F 90 classification
- Expert opinion by an official material testing institute

**Construction & Equipment**

- Container of high mechanical resistance
- Single layer wall structure of homogeneous solid material
- Galvanized base drip pan for environmental protection according to the
- Water Resources Law § 19
- Dimensions optimized for IBC containers and Euro pallets
- Door(s) with 3D stainless steel strips, 3-point locking system and profile semi-cylinder
- Electrical door hold-open system with flexible and adjustable door opening angle up to 120°
- Smoke triggered fire detection for automatic door closure
- Closing sequence control
- Explosion-protected electrical system
- Ventilation openings on the top side, DN 100 - closure via fire dampers
- Shelves with hot-dip galvanised grates

**Type**

- PRIOCONT 2-IBC

**Material & Surface**

- Standard surface CP laminate
- Building material with surface coating, classified A2 – s1, d0: non-combustible
- Colour light grey, similar to RAL 7035

**Scope of delivery**

- Sump
- Tandem door closer
- Door coordinator incl. door damper

**Options**

- Doors or entire body in alternative RAL colours / surfaces, on request
- Design with anti-burglary protection according to WK 2
- Fire-resistant cable compartment
- Single cable and pipe-penetration

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

- Panic hardware with panic function B "standard"
- Assembly on-site

Element-External dimension  
(H x B x T) in mm: .....

Surface: .....

Weight: .....

Storage volume number IBC: .....

Storage volumen number euro palette:  
.....

Storage volumen number drums: .....

Options: .....

**Typ: PRIOCONT**

**Fabrikat: PRIORIT AG**  
[www.priorit.de](http://www.priorit.de)  
**Tel.: 06181 / 3640 0**  
**Fax : 06181 / 3640 230**