LV: Datum: 07.03.22
Objekt: Seite: 1

# Pos. Stück Leistungsbeschreibung E-Preis G-Preis

## 10 1 PRIOROOM Fire Resistant Room

Fire resistant room to store large quantities of hazardous materials, or for enclosure of previously constructed production systems during ongoing operation. The modular system consists of prefabricated elements just 42 mm thick, and can be used to create a separate fire compartment quickly and cleanly, ensuring simple set-up, modification, and expansion. Homogeneous, solid material has high-quality, easy to clean interior and exterior surfaces. The room has no threshold in the entryway area, and can be equipped with commonly available collection basins according to the regulations of the WHG (Water Resources Act). The room offers a fire resistance of 90 minutes.

#### **Function**

- Fire resistance 90 minutes: fire-resistant
- Wall: El 90 classification
- Ceiling: F 90/EI 90 a→b
- T 90-RS classification of door(s)
- Door(s) are smoke-tight, tested for continuous operation

#### **Construction & Equipment**

- Room with high mechanical resistance
- Barrier-free access with pallets, drums and compressed gas cylinders
- Door(s) with 3D stainless steel strips, 3-point locking system, prepared for profile cylinder
- Suitable for the storage and removal of flammable liquids, acids and alkalis
- Room may be equipped with lighting, ventilation equipment, racks and drip pans
- · Delivered on pallets, assembly on site

#### **Material & Surface**

- Building material with surface coating on both sides,
- classified A2 s1, d0 non-combustible
- Standard surface CP laminate
- Colour light grey, similar to RAL 7035, edges and bevels in
- different colour

### **Options**

- Doors or entire body in alternative RAL colours / surfaces, on request
- Smoke proof
- Ventilation flap
- Fire resistant cable compartment
- Door hold-open device
- Explosion protected smoke detector
- Door handles, locking cylinder
- Door damper
- Door closer for single leaf doors
- Door closer for double leaf doors
- Panic hardware with panic function B
- Electronic door closing systems

LV: Datum: 07.03.22
Objekt: Seite: 2

# Pos. Stück Leistungsbeschreibung E-Preis G-Preis

PRIOROOM GSL is offered on a project-by-project basis

Element-External dimension (H x B x T) in mm:		
Surface:		
Door stop (DIN L / DIN R):		
Number door:		
Door clearance height in mm:		
Door clearance width in mm:		
Number door leaf:		
Number fixed leaf:		
Number active leaf:		
Storage volume	en number euro pal	ette:
Storage volumen number drums:		
Options:		
Тур:	PRIOROOM	
Fabrikat:	PRIORIT AG www.priorit.de Tel.: 06181 / 3640	<b>)</b> 0

Fax: 06181/3640230