PRIOCAB Typ30

Under-table safety cabinet according to DIN EN 14470-1













Fire resistant under table type 30 safety cabinet for proper storage of flammable liquids and solid materials in work areas.

Type 30 safety cabinets, tested and certified in accordance with EN 14470-1, offer a fire resistance rating of 30 minutes, and are GS (geprüfte Sicherheit - tested safety) certified.

The single-layer structure of the body and door give the cabinet a high level of mechanical strength. The high-quality interior and exterior surfaces are easy to clean.

24

Function

- Fire resistance 30 minutes
- GS Certificates
- Safety cabinet Typ30 according to EN 14470-1
- Suitable for the storage of inflammable fluids

Technical modifications reserved. | Version: 16.10.2023





Hydraulic door closer



Removable shelf



Drain pan with perforated plate insert

Construction & Equipment


- Under-table safety cabinet with high-quality surface inside and outside
- Single-layer wall construction
- Double-leaf version (width 1100 mm)
- In case of fire, self-closing ventilation openings at the rear, connections DN 100 mm
- Door closer with integrated hold-open system and thermocouples for automatic door closure in the event of fire
- Different equipment variants
- Fittings adjustable in 32 mm hole spacing
- Floor pan with perforated plate insert for use as a fourth storage level
- Grounded tank bottom, tilt resistant with a central hole for systematic removal of leakage


Material & Surface

- Homogeneous building material, single-layer construction
- Standard surface CP laminate
- Surface light grey, similar to RAL 7035
- Easy to clean



Application examples





EN32U.063.110

1 floor pan with perforated plate insert

EN32U.063.110-1A

1 Fully-extendable shelf

Art.	Code	H x W x D mm	H x W x D mm	kg kg	∨ ≈	Features	Material	
	cabin «	et 2-leaf, Type 30 w 375 x 980 x 472	ith door closer and hole 635 x 1100 x 550	d-open sy 90	stem 24	1 tank bottom, 1 perforated plate insert	Sheet steel, powder coated, RAL 7035	
Under-table safety cabinet 2-leaf, Type 30 with door closer, hold-open system and pull-out shelves								
EN32U.063.110-1A	K	375 x 980 x 472	635 x 1100 x 550		19	1 fully-extendable shelf, load capacity 75 kg	Sheet steel, powder coated, RAL 7035	

1Colour codo v.

1 = Doors and plinth panel in yellow, similar to RAL 1023

without = Standard product, light grey, similar to RAL 7035

Order example:

EN32U.063.110-1A-1 → Under-table safety cabinet 2-leaf, Type 30 with door closer, hold-open system and pull-out shelves, doors and plinth panel painted on the outside in RAL 1023

26 Hazardous material storage www.priorit.de

Options and accessories

- Doors and entire body in alternative RAL colours / surfaces, on request
- Tank bottoms, max. load 75 kg
- Fully extendable shelf, max. load 75 kg
- Load increase to 150 kg
- Floor pan incl. perforated plate insert
- Perforated plate insert
- Fine (pre)filter for EBEL:VENT-EN-U (replacement)
- Replacement active charcoal filter for EBEL:VENT-EN-U
- Recirculated air attachment, ready to plug in



EBEL:VENT-EN-URecirculated air attachment
Technical specifications see page: 16

Art.	Accessories)
		H x W x D mm
Supplementary equi	pment for Under-table safety cabinet Typ30, double-leaf	
EN32U-WB0	Tank bottom, configuration in steel sheet RAL 7035	36 x 977 x 467
EN32U-BOW	Floor pan incl. perforated plate insert, configuration in steel sheet RAL 7035, powder-coated	60 x 977 x 447
EN32U-LBE	Perforated plate insert, configuration in steel sheet RAL 7035, powder-coated	60 x 955 x 425
EN32U-AZ	Fully-extendable shelf, steel sheet, powder-coated, RAL 7035 (load capacity 75 kg, 19 litre collection capacity)	
Artificial ventilation		
EBEL:VENT-EN-U	Recirculated air attachment, ready to plug in incl. adapter set and connection hose	
HF.SF.9405	Fine (pre)filter for EBEL:VENT-EN-U (replacement)	
HF.AK.9404	Replacement active charcoal filter for EBEL:VENT-EN-U	