

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10      1      **PRIODOOR RTX – 30 minutes  
Inspection opening closure**

Universal inspection opening closure for flush mounting in shaft walls, solid walls and PRIOWALL. The closure is available single-leaf or double-leaf and is suitable for large-scale compliant partitioning of installation shafts and the partitioning of measuring equipment and distributors in escape and rescue routes. The inspection opening closure is tightly sealed all around and offers fire resistance for 30 minutes.

The product was equipped with a deadbolt lock without latch. This means that the inspection opening catch cannot fall into the lock and can be easily pressed open from the inside.

**Function**

- 30 minutes fire resistance, fire retardant
- EI 30 i→o, classification
- Flammability according to DIN 4102 Part 2 (ETK) over 30 minutes
- Tested fire behaviour from the inside of the chamber to the outside for at least 30 minutes, based on the standard fire in accordance with DIN 4102 Part 2
- Compliance with temperature values max. 140 K on average, max. 180 K at points
- Verification of usability, technical group Z-6.55-
- Smoke protection
- Leak-proof closing
- Sound reduction index depending on size up to 40 dB

**Construction**

- Inspection opening closure with high mechanical resistance
- Flush mounting or for installation on the wall
- Single and double-leaf design
- Circumferential block frame 43 mm wide
- Circumferential smoke and fire seals, expand automatically in the event of a fire
- Door closes flush with frame, opening angle ca. 180°
- Mortise lock, Locking system with single cylinder
- Door stop position DIN right / DIN left on request
- Door detachable
- Door hinges in stainless steel

**Material characteristic**

- Non-combustible board with surface coating, classification A2 – s1, d0
- Standard laminate surface
- Colour light grey, similar to RAL 7035, edges and bevels in different colour

**Scope of delivery**

- PRIODOOR RTX as a kit

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

**Options**

- PRIODOOR RTX with wall
  - 4-sided wall for hanging installation
  - 3-sided wall for standing installation
- Standardised colours - white, similar to RAL 9016; decor brushed aluminium; primer foil
- Continuous decors possible
- Fixing material
- Door lock cylinder rosette
- Single cylinder 30/10, senate closure
- Single cylinder keyed-differently without rosette
- Magnet Reed Contact Set

Element-External dimension

(H x B x T) in mm: .....

Rough opening

(H x B) in mm: .....

Surface: .....

Wall type: .....

Mounting type:

- Flush mounting
- On-wall mounting

With wall:

- 4-sided wall for hanging installation
- 3-sided wall for standing installation

Options: .....

**Typ: PRIODOOR RTX EI30**

**Fabrikat:**

**PRIORIT AG**  
[www.priorit.de](http://www.priorit.de)  
**Tel.: +49 6181 3640-0**  
**Fax : +49 6181 3640-210**