

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIODOOR ETX A – 90 minutes**
Inspection opening closure, flush with the adjacent areas

Inspection opening closure for flush mounting in GRP shaft walls with no visible frame. The lockable and sealed door with an aluminum frame that can be plastered over is suitable for compliant partitioning of small and large installation shafts and the partitioning of measuring equipment and distributors in escape and rescue routes. Quick and easy installation for easy access to shaft. The closure is tightly sealed all around and offers a fire resistance of 90 minutes.

Function

- 90 minutes fire resistance, fire resistant
- EI 90 i→o classification
- Flammability according to DIN 4102 Part 2 (ETK) over 90 minutes
- Tested fire behaviour from the inside of the chamber to the outside for at least 90 minutes, based on the standard fire in accordance with DIN 4102 Part 2
- Compliance with temperature values max. 140 K on average, max. 180 K at points
- Verification of usability, technical group Z-6.55-
- Smoke protection
- Leak-proof closing

Construction

- Inspection door with high mechanical resistance
- Flush mounting in 2 x 20 mm GRP shaft wall or 2 x 25 mm when planked
- Installed depth < 100 mm in metal stud wall
- Single-leaf design, Door stop position DIN right
- Circumferential aluminium frame with plaster edge
- Circumferential smoke and fire seals, expand automatically in the event of a fire
- Door closes flush with frame, opening angle ca. 180°
- Locking system with single cylinder

Material characteristic

- Non-combustible board with surface coating, classification A2 – s1, d0
- Standard CPL surface
- Colour light grey, similar to RAL 7035, edges and bevels in different colour
- Green Building Declaration according to LEED and DGNB

Scope of delivery

- Door leaf with stainless steel hinges and box staple
- Aluminium frame, corner connection, fire and smoke seal
- Profile single cylinder
- Torque plate and fastening clip, Assembly blocks

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Options

- Standardised colours - white, similar to RAL 9016; decor brushed aluminium; primer foil
- Special decors / special colours
- Door lock cylinder rosette
- Profile single cylinder – simultaneous locking

Element-External dimension
(H x B) in mm:

Rough opening BRM
(H x B) in mm:

Surface:

Wall type:

Options:

Typ: PRIODOOR ETX A 90

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: +49 6181 3640-0
Fax : +49 6181 3640-230