

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIODOOR ETX – 30 minutes**
Inspection opening closure for special solutions

All-round tightly closing inspection opening closure for flush mounting in the installation shaft wall, optionally as shoring on the installation shaft wall. The closure is available single-leaf or double-leaf and is suitable for large-scale compliant partitioning of installation shafts and the partitioning of measuring equipment and distributors in escape routes. The closure is tightly sealed all around and offers a fire resistance of 30 minutes.

Function

- 30 minutes fire resistance, fire retardant
- EI 30 i→o, classification
- Flammability according to DIN 4102 Part 2 (ETK) over 30 minutes
- Tested fire behaviour from the inside of the chamber to the outside for at least 30 minutes, based on the standard fire in accordance with DIN 4102 Part 2
- Compliance with temperature values max. 140 K on average, max. 180 K at points
- Verification of usability, technical group Z-6.55-
- Smoke protection
- Leak-proof closing

Construction

- Inspection opening closure with high mechanical resistance
- Flush mounting or for installation on the wall
- Single and double-leaf design
- Circumferential block frame 55 mm wide, 42 mm deep
- Circumferential smoke and fire seals, expand automatically in the event of a fire
- Door closes flush with frame, opening angle ca. 180°
- Single to triple latch lock, depending on door height
- Locking system with single cylinder
- Door stop position DIN right, optionally DIN left

Material characteristic

- Non-combustible board with surface coating, classification A2 – s1, d0
- Standard CPL surface
- Colour light grey, similar to RAL 7035, edges and bevels in different colour
- Green Building Declaration according to LEED and DGNB

Scope of delivery

- PRIODOOR ETX as a kit

Options

- PRIODOOR ETX with with three-sided frame and lowerable floor sealing
- PRIODOOR ETX-AW – Mounting on the wall
- Door handle set
- Automatic multipoint lock with panic function E
- Hinged ring handle
- Ventilation modul

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

- Mounting hardware for solid wall and GRP-shaft wall; flush installation
- Mounting hardware for solid wall and GRP-shaft wall; mounting on the wall
- Magnet Reed Contact Set

Element-External dimension

(H x B x T) in mm:

Rough opening

(H x B) in mm:

Surface:

Wall type:

Three-sided frame and lowerable floor sealing:

.....

Options:

Typ: PRIODOOR ETX 30

Fabrikat: PRIORIT AG

www.priorit.de

Tel.: +49 6181 3640-0

Fax : +49 6181 3640-230