

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIODOOR EVX – 30 Minutes
Fire protection barrier, Surface-Mounted**

Universally usable fire protection barrier with installation frame for easy wall installation. The fire protection barrier is ideally suited for the small-surface to large-scale bulkheading of in-wall and panel distributors in rescue routes. The closure is tightly sealed all around and offers a fire resistance of 30 minutes.

Function

- 30 minutes fire resistance, fire retardant
- Smoke protection

Construction

- Fire-protection barrier for full-surface wall installation
- With circumferential, pre-drilled mounting frame, 22 mm material thickness, 115 mm wide
- Mounting on solid wall
- 2-point door locking device with turning lever and single cylinder,
- can be integrated into the building locking system
- Single leaf door with stop position DIN right
- Double-leaf design up to H x W 2500 mm x 2300 mm
- Circumferential smoke and fire seals, automatically expand in the event of a fire
- Mounting directly on the wall with pre-drilled holes in mounting frame
- Door leaf easy to hinge and unhinge

Material characteristic

- Non-combustible board with surface coating, classification A2 – s1, d0
- Standard CPL surface
- Colour light grey, similar to RAL 7035, edges and bevels in different colour
- Green Building Declaration according to LEED and DGNB

Scope of delivery

- PRIODOOR EVX with mounting frame
- Mounting hardware for solid wall

Options

- Standardised colours - white, similar to RAL 9016; decor brushed aluminium; primer foil
- Special decors / special colours
- Up to 3-fold doubling of the frame to cover protruding elements

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Element-External dimension
(H x B x T) in mm:

Rough opening
(H x B) in mm:

Surface:

Weight:

Wall type:

Options:

Typ: PRIODOOR EVX

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: +49 6181 3640-0
Fax : +49 6181 3640-230