

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

1 1 **PRIOWALL – 90 minutes
Wall System**

Single-layer, fire-resistant wall system with various surfaces for the formation of interior partitions for room closures, fire areas, etc. The PRIOWALL wall system consists of coated non-flammable wall panels of 42 mm in thickness, which can be easily and neatly constructed, converted and expanded using various joining technologies.

PRIOWALL is a component of the „System 42“ modular fire protection system and is suited for the installation of PRIORIT system components such as fire-protection closures, inspection opening closures, smoke-extraction flaps, fire dampers and bulkheads or ventilation elements.

Function

- 90 minutes fire resistance, fire resistant
- EI 90 classification

Construction

- Single-ply, highly stable prefabricated elements
- Construction possible in I-shape, L-shape and U-shape
- Planning on a project-by-project basis, manufacturing and installation
- Overall height up to 4 m, unlimited width
- Ceiling construction with PRIOCEIL

Material characteristic

- Non-combustible board with surface coating, classification A2 – s1, d0
- Standard CPL surface
- Colour light grey, similar to RAL 7035, edges and bevels in different colour

Installation of System42 Components

- Wall system PRIOWALL
- Fire Resisting Closure PRIODOOR FSA
- Inspection Door PRIODOOR ETX / PRIODOOR RTX
- Smoke damper PRIODOOR ETX RDA (vertical/horizontal)

Accessoires

- Fire protection glasses for inspection closure and door
- Cable and pipe bulk head for wall
- Ventilation systems for PRIOWALL / PRIODOOR ETX / PRIODOOR RTX
- Standardised colours - white, similar to RAL 9016; decor brushed aluminium; primer foil
- Special decors / special colours / veneer surfaces

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Element-external dimension
(H x B) in mm:

Surface:

Shape:

Door stop (DIN L / DIN R):

Number door leaf:

Number fixed leaf:

Number traffic leaf:

Number PRIODOOR ETX/RTX 1-flg.:

Number PRIODOOR ETX/RTX 2-flg.:

Dimension PRIODOOR ETX/RTX 1-flg.:
(H x B) in mm:

Dimension PRIODOOR ETX/RTX 2-flg.:
(H x B) in mm:

Number PRIODOOR FSA 1-flg.:

Dimension PRIODOOR FSA 1-flg.:
(H x B) in mm

Number PRIODOOR FSA 2-flg.:

Dimension PRIODOOR FSA 2-flg.:
(H x B) in mm

Number PRIODOOR ETX RDA:

Dimension PRIODOOR ETX RDA:
(H x B) in mm

Number PRIODOOR ETX RDA H:

Dimension PRIODOOR ETX RDA H:
(H x B) in mm

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

More options

Fire protection glasses:

Dimension fire protection glasses:
(H x B) in mm

Cable and pipe bulk head:

Ventilation systems:

Notice:
.....
.....
.....

Typ: PRIOWALL 90

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: +49 6181 3640-0
Fax : +49 6181 3640-210