

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10      1      **PRIODOOR FSA TUN**  
**Single and two-leaf tunnel operating doors**

Pressure and suction-stable door for use in company buildings, technical rooms etc. Design according to Directive 2004/54/EC, RABT, RVS, ZTV-ING part 5 and TL/TP TTT. The design considers the special requirements for technical equipment used in the operation of road tunnels in Austria.

**Function**

- Fire resistance 90 minutes: fire-resistant
- T 90 classification
- Smoke-tight and tested for continuous operation
- Protection rating in accordance with IP 54
- Stable against pressure / suction up to 2000 Pa

**Construction**

- Single and double-leaf fire-resisting closure
- Solid door leaf with stainless steel surface on the inside and outside
- Circumferential block frame on three or four sides with stainless steel surface
- Adjustable stainless steel hinges
- Locking with three bolt lock
- Self-closing via adjustable overhead door closers (active leaf)
- Fixed-leaf with gate espagnolettes
- Multistage fire protection seal, autonomously expands in case of fire
- Monitorable door status by inductive proximity switch
- Equipotential bonding

**Material characteristic**

- Building material A2 – s1, d0 non-combustible
- Building material is chemically highly stable, solid, stable and moisture-resistant
- Surface on both sides in stainless steel 1.4571, material characteristic according to ZTV-ING Part 5, requirement class I,
- Strike plates in stainless steel 1.4571

**Scope of delivery**

- Door PRIODOOR FSA TUN
- Mounting material

**Options**

- Monitorable bolt contact
- Special sizes on request
- Emergency release
- Door closer with closing sequence control

**Variants – single-leaf**

- Exterior height of element: 1811 – 2500 mm
- Exterior width of element: 480 – 1250 mm

**LV:**  
**Objekt :**

**Datum: 03.08.16**  
**Seite: 2**

<b>Pos.</b>	<b>Stück</b>	<b>Leistungsbeschreibung</b>	<b>E-Preis</b>	<b>G-Preis</b>
-------------	--------------	------------------------------	----------------	----------------

**Variants – double-leaf**

- Exterior height of element: 1811 – 2500 mm
- Exterior width of element: 480 – 2500 mm

**Typ: PRIODOOR FSA TUN**

**Fabrikat: PRIORIT AG**  
[www.priorit.de](http://www.priorit.de)  
**Tel.: 06181 / 3640 0**  
**Fax : 06181 / 3640 230**

**LV:**  
**Objekt :**

**Datum: 03.08.16**  
**Seite: 3**

<b>Pos.</b>	<b>Stück</b>	<b>Leistungsbeschreibung</b>	<b>E-Preis</b>	<b>G-Preis</b>
-------------	--------------	------------------------------	----------------	----------------