

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIODOOR ETX TUN**
Tunnel Electro-Recess Closure Flush with the Adjacent Area

Standardized, fire-resistant maintenance door, flush with the adjacent areas for the separation of safety-related relevant electrical installations in Tunnel niche. This door is suitable for securing the maintenance of performance function of safety-related electrical wiring systems and distributors for the emergency lighting and smoke clearance system. Design according to Directive 2004/54/EG, RABT, ZTV-ING Part 5.

Function

- Fire resistance 90 minutes: fire-resistant
- EI 90/F 90 classification
- Smoke protection
- Safety class I
- Protection rating in accordance with IP 54
- Stable against pressure / suction up to 1000 Pa

Construction

- Single and double-leaf maintenance cover for flush installation in tunnel recess
- Fastening laterally inside with cable tie mount
- Door closes flush with frame
- Door opening angle ca. 90°
- Door hinges in stainless steel 1.4571
- Turning lever in stainless steel 1.4401 prepared for DIN single cylinder
- Fire barrier with circumferential fire, smoke and dust proof seals
- Equipotential bonding
- Integrated door check strap
- With inductive proximity switch for door monitoring, 90° rotatable

Material characteristic

- Building material with surface coating, classified A2 – s1, d0 non-combustible
- Building material and surface is chemically highly stable and moisture-resistant
- Outside surface in stainless steel 1.4571
- Inside surface synthetic-coated
- Cable tie mount in stainless steel 1.4529
- Door hinges in stainless steel 1.4571
- Turning lever in stainless steel 1.4401

Scope of delivery

- Maintenance cover, fastening material, prepared for connection to equipotential bonding

Options

- Outside surface powdered according to RAL
- Special sizes, special designs on request
- Lateral impact protection for front-panel mounting in the escape route

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Element-External dimension
(H x B x T) in mm:

Rough opening
(H x B) in mm:

Shape:

Surface:

Weight:

Wall type:

Door clearance height in mm:

Door clearance width in mm:

Options:

Typ: PRIODOOR ETX TUN

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: 06181 / 3640 0
Fax : 06181 / 3640 230